



Manufactured For:

**GfG Instrumentation**

1194 Oak Valley Drive, Suite 20, Ann Arbor, Michigan 48106 USA • 800-959-0529 • 734-769-0573 • 734-769-1888 Fax

Worldwide Manufacturer of Gas Detection Solutions

Page 1/10

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

### 1 Identification

· **Product Identifier**

· **Trade name: Precision Calibration Gas Mixture**

· **Product Number:** G-5615

· **Relevant identified uses of the substance or mixture and uses advised against:**

Used for calibration of gas measuring devices. Not suitable for human consumption.

· **Product Description** Calibration gas mixture consisting of Sulfur Dioxide and Nitrogen.

· **Details of the Supplier of the Safety Data Sheet:**

· **Manufacturer/Supplier:**

Gasco Affiliates, LLC

320 Scarlett Blvd.

Oldsmar, FL 34677

TELEPHONE NUMBER: (800) 910-0051

FAX NUMBER: (866) 755-8920

E-MAIL: info@gascogas.com

· **Emergency telephone number:**

Inside the US: 1-800-424-9300 (CHEMTREC, 24 hours)

Outside the US: 1-703-527-3887 (CHEMTREC, 24 hours)

### 2 Hazard(s) Identification

· **Classification of the substance or mixture:**



GHS04 Gas cylinder

Press. Gas

H280 Contains gas under pressure; may explode if heated.



GHS07

Skin Irrit. 2

H315 Causes skin irritation.

Eye Irrit. 2A

H319 Causes serious eye irritation.

Simple Asphyxiant

May displace oxygen and cause rapid suffocation.

· **Label elements:**

· **GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

· **Hazard pictograms:**



GHS04 GHS07

· **Signal word:** Warning

· **Hazard-determining components of labeling:**

Nitrogen

Sulfur Dioxide

· **Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

(Contd. on page 2)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**

H315 Causes skin irritation.

H319 Causes serious eye irritation.

May displace oxygen and cause rapid suffocation.

**Precautionary statements:**

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

P410+P403 Protect from sunlight. Store in a well-ventilated place.

**Unknown acute toxicity:**

99.3 % of the mixture consists of component(s) of unknown toxicity.

**Classification system:****NFPA ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

The substance possesses oxidizing properties.

**HMIS-ratings (scale 0 - 4)**

Health = 1

Fire = 0

Reactivity = 0

**Hazard(s) not otherwise classified (HNOC):** None known**3 Composition/Information on Ingredients****Chemical characterization: Mixtures****Description:** Mixture of substances listed below with non-hazardous additions.**Dangerous Components:**

CAS: 7727-37-9	Nitrogen	99.25 - 99.99995%
RTECS: QW 9700000	⚠ Press. Gas, H280; Simple Asphyxiant	
CAS: 7446-09-5	Sulfur Dioxide	0.00005 - 0.75%
	⚠ Acute Tox. 3, H331; ⚠ Skin Corr. 1B, H314; Press. Gas, H280	

**4 First-Aid Measures****Description of first aid measures:****General information:**

Symptoms of poisoning may occur after exposure to dust, fumes or particulates; seek medical attention if feeling unwell.

**After inhalation:**

Supply fresh air. If required, provide artificial respiration. Consult doctor if symptoms persist.

In case of unconsciousness place patient stably in side position for transportation.

**After skin contact:**

Immediately wash skin with soap and plenty of water for at least 20 minutes.

(Contd. on page 3)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**

If skin irritation occurs, consult a doctor.

In cases of contact with liquified material, frostbite may occur. Immerse frostbite in cool-warm water and seek medical attention.

· **After eye contact:**

Rinse opened eye for several minutes under running water. If symptoms persist, consult a doctor.

· **After swallowing:** Not a normal route of entry.

· **Information for doctor:**

· **Most important symptoms and effects, both acute and delayed:** No further relevant information available.

· **Indication of any immediate medical attention and special treatment needed:**

No further relevant information available.

· **Extinguishing media:**

· **Suitable extinguishing agents:**

Use fire fighting measures that suit the environment.

Use water spray to cool fire-exposed containers.

· **Special hazards arising from the substance or mixture:**

Closed containers may explode when exposed to extreme heat.

If incinerated, product will release the following toxic fumes: Oxides of Nitrogen (NOx) and Sulfur.

· **Advice for firefighters:**

This gas mixture is not flammable; however, containers, when involved in fire, may rupture or burst in the heat of the fire.

· **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent) and full protective gear to prevent contact with skin and eyes.

· **Personal precautions, protective equipment and emergency procedures:**

In a confined area, NIOSH approved respiratory protection may be required.

Wear protective equipment. Keep unprotected persons away.

Ensure adequate ventilation.

Keep people at a distance and stay upwind.

Treat any fumes as toxic.

· **Environmental precautions:** Inform authorities in case of gas release.

· **Methods and material for containment and cleaning up:**

Dispose contaminated material as waste according to section 13.

Ensure adequate ventilation.

Dispose of the collected material according to regulations.

· **Reference to other sections:**

See Section 7 for information on safe handling.

See Section 8 for information on personal protection equipment.

See Section 13 for disposal information.

· **Handling**

· **Precautions for safe handling:**

Ensure good ventilation/exhaustion at the workplace.

Open and handle receptacle with care.

(Contd. on page 4)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor.

Be aware of any signs of dizziness or fatigue; exposures to fatal concentrations of this gas mixture could occur without any significant warning symptoms due to the potential for oxygen deficiency (simple asphyxiation). Do not attempt to adjust, repair or in any other way modify the cylinders containing this gas mixture. If there is a malfunction or another type of operational problem, contact nearest distributor immediately.

- **Information about protection against explosions and fires:**

Pressurized container: protect from sunlight and do not expose to temperatures exceeding 50 °C, i.e. electric lights. Do not pierce or burn, even after use.

Keep protective respiratory device available.

Do not cut, grind or weld on container that contains or contained product.

Do not spray on a naked flame or any incandescent material.

- **Conditions for safe storage, including any incompatibilities:**

Store away from strong oxidizing agents, strong reducing agents and Zinc

- **Storage**

- **Requirements to be met by storerooms and receptacles:**

Store in a cool location.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-in, first-out" inventory system to prevent full containers from being stored for long periods of time.

Cylinders should be firmly secured to prevent falling or being knocked over. Cylinders must be protected from the environment, and preferably kept at room temperature. Cylinders should be stored in dry, well-ventilated areas, away from sources of heat, ignition, and direct sunlight. Protect cylinders against physical damage. Full and empty cylinders should be segregated. Use a "first-in, first-out" inventory system to prevent full containers from being stored for long periods of time.

- **Information about storage in one common storage facility:** Not required.

- **Further information about storage conditions:** Store in cool, dry conditions in well sealed receptacles.

- **Specific end use(s):** No further relevant information available.

- **Additional information about design of technical systems:** No further data; see section 7.

- **Control parameters:**

All ventilation should be designed in accordance with OSHA standard (29 CFR 1910.94). Use mechanical (general) ventilation for storage areas. Use appropriate ventilation as required to keep Exposure Limits in Air below TLV & PEL limits.

- **Components with occupational exposure limits:**

**7727-37-9 Nitrogen**

TLV withdrawn TLV, see App. F; simple asphyxiant

**7446-09-5 Sulfur Dioxide**

PEL Long-term value: 13 mg/m<sup>3</sup>, 5 ppm

REL Short-term value: 13 mg/m<sup>3</sup>, 5 ppm

Long-term value: 5 mg/m<sup>3</sup>, 2 ppm

TLV Short-term value: 0.65 mg/m<sup>3</sup>, 0.25 ppm

- **Additional information:** The lists that were valid during the creation of this SDS were used as basis.

(Contd. on page 5)



**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**

- **Exposure controls:**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
Keep away from foodstuffs, beverages and feed.  
Wash hands before breaks and at the end of work.  
Immediately remove all soiled and contaminated clothing and wash before reuse.
- **Breathing equipment:**



Suitable respiratory protective device recommended.

- **Protection of hands:**



Protective gloves

- **Material of gloves:**  
The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material cannot be calculated in advance and has therefore to be checked prior to the application.
- **Penetration time of glove material:**  
The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.
- **Eye protection:**



Tightly sealed goggles

**9 Physical and Chemical Properties**

- **Information on basic physical and chemical properties**
- **General Information**
- **Appearance:**

<b>Form:</b>	Gaseous
<b>Color:</b>	Clear, colorless
- **Odor:** Rotten
- **Odor threshold:** Not determined.
- **pH-value:** Not determined.
- **Change in condition**

<b>Melting point/Melting range:</b>	Not determined.
<b>Boiling point/Boiling range:</b>	Not determined.
- **Flash point:** None
- **Flammability (solid, gaseous):** Product is not flammable.
- **Ignition temperature:**

<b>Decomposition temperature:</b>	Not determined.
-----------------------------------	-----------------

(Contd. on page 6)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**

- **Auto igniting:** Product is not self-igniting.
- **Danger of explosion:** Not determined.
- **Explosion limits:**
  - Lower:** Not determined.
  - Upper:** Not determined.
- **Vapor pressure:** Not determined.
- **Density:**
  - Relative density:** Not determined.
  - Vapor density:** Not determined.
  - Evaporation rate:** Not applicable.
- **Solubility in / Miscibility with:**
  - Water:** Not miscible or difficult to mix.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 0.0 %
- **Other information:** No further relevant information available.

- 
- **Reactivity:** No further relevant information available.
  - **Chemical stability:** Stable under normal conditions.
  - **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
  - **Possibility of hazardous reactions:** No dangerous reactions known.
  - **Conditions to avoid:** No further relevant information available.
  - **Incompatible materials:** Strong oxidizing agents, strong reducing agents and Zinc.
  - **Hazardous decomposition products:** Nitrogen Oxides (NO<sub>x</sub>) and Sulfur Oxides.
- 

- **Information on toxicological effects:**
- **Acute toxicity:**
- **LD/LC50 values that are relevant for classification:**
  - 7446-09-5 Sulfur Dioxide**
  - Inhalative LC50/4 h 5040 mg/l (rat)
- **Primary irritant effect:**
- **On the skin:** Causes skin irritation
- **On the eye:** Direct contact may cause eye irritation.
- **Additional toxicological information:**
  - The product shows the following dangers according to internally approved calculation methods for preparations:
- **Carcinogenic categories:**
- **IARC (International Agency for Research on Cancer):**
  - Group 1 - Carcinogenic to humans
  - Group 2A - Probably carcinogenic to humans
  - Group 2B - Possibly carcinogenic to humans

(Contd. on page 7)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**

Group 3 - Not classifiable as to its carcinogenicity to humans

Group 4 - Probably not carcinogenic to humans

7446-09-5 Sulfur Dioxide

3

**· NTP (National Toxicology Program):**

None of the ingredients are listed.

**· OSHA-Ca (Occupational Safety & Health Administration):**

None of the ingredients are listed.

**12 Ecological Information**

- **Toxicity:** The hazards for the aquatic environment are unknown.
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability:** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential:** No further relevant information available.
- **Mobility in soil:** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Generally not hazardous for water.
- **Results of PBT and vPvB assessment:**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects:** No further relevant information available.

**13 Disposal Considerations**

- **Waste treatment methods:**
- **Recommendation:**  
Release all residual gas pressure in a well ventilated area. Verify the cylinder is completely empty (0 PSIG). Remove or cover any hazard labels. Return empty cylinder for recycling.  
NOTE: Check with the local waste authority before placing any gas cylinder into waste container for pickup. GASCO encourages the consumer to return all cylinders.
- **Waste disposal key:**  
The U.S. EPA has not published waste disposal numbers for this product's components.
- **Uncleaned packagings**
- **Recommendation:** Return cylinder and unused product to supplier.

**14 Transport Information**

- **UN-Number:**
- **DOT, ADR, IMDG, IATA** UN1956
- **UN proper shipping name:**
- **DOT** Compressed gas, n.o.s.
- **ADR** UN1956 Compressed gas, n.o.s.
- **IMDG, IATA** COMPRESSED GAS, N.O.S.
- **Transport hazard class(es):**
- **DOT**



- **Class:** 2.2

(Contd. on page 8)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**· **Label:** 2.2· **ADR**· **Class:** 2.2 1A· **Label:** 2.2· **IMDG, IATA**· **Class:** 2.2· **Label:** 2.2· **Packing group:**· **DOT, ADR, IMDG, IATA** Non-Regulated Material· **Environmental hazards:** Not applicable.· **Special precautions for user:** Not applicable.· **Danger code (Kemler):** 20· **EMS Number:** F-C,S-V· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code:** Not applicable.· **Transport/Additional information:**· **DOT**· **Quantity limitations:** On passenger aircraft/rail: 75 kg  
On cargo aircraft only: 150 kg· **ADR**· **Excepted quantities (EQ):** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml· **IMDG**· **Limited quantities (LQ):** 120 ml· **Excepted quantities (EQ):** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml· **UN "Model Regulation":** UN1956, Compressed gas, n.o.s., 2.2**15 Regulatory Information**· **Safety, health and environmental regulations/legislation specific for the substance or mixture:**· **SARA (Superfund Amendments and Reauthorization):**· **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

· **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

(Contd. on page 9)



**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture****· TSCA (Toxic Substances Control Act):**

All ingredients are listed or exempt from listing.

**· California Proposition 65:****· Chemicals known to cause cancer:**

None of the ingredients are listed.

**· Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

**· Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

**· Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

**· Carcinogenic categories:****· EPA (Environmental Protection Agency):**

None of the ingredients are listed.

**· TLV (Threshold Limit Value established by ACGIH):**

None of the ingredients are listed.

**· NIOSH-Ca (National Institute for Occupational Safety and Health):**

None of the ingredients are listed.

**· GHS label elements**

The substance is classified and labeled according to the Globally Harmonized System (GHS).

**· Hazard pictograms:**

GHS04 GHS07

**· Signal word: Warning****· Hazard-determining components of labeling:**

Nitrogen

Sulfur Dioxide

**· Hazard statements:**

H280 Contains gas under pressure; may explode if heated.

H315 Causes skin irritation.

H319 Causes serious eye irritation.

May displace oxygen and cause rapid suffocation.

**· Precautionary statements:**

P280 Wear protective gloves.

P280 Wear eye protection / face protection.

P264 Wash thoroughly after handling.

P305+P351+P338 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

P321 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).

P332+P313 If skin irritation occurs: Get medical advice/attention.

P337+P313 If eye irritation persists: Get medical advice/attention.

P302+P352 IF ON SKIN: Wash with plenty of water.

P362+P364 Take off contaminated clothing and wash it before reuse.

(Contd. on page 10)

**Safety Data Sheet (SDS)**

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Issue date 08/29/2016

Reviewed on 08/29/2016

**Trade name: Precision Calibration Gas Mixture**

P410+P403 Protect from sunlight. Store in a well-ventilated place.

**National regulations:**

The product is subject to be classified according with the latest version of the regulations on hazardous substances.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

\*

**Relevant phrases:**

Gasco Affiliates, LLC, makes no express or implied warranties, guarantees or representations regarding the product of the information herein, including but not limited to any implied warranty or merchantability or fitness for use. Gasco Affiliates, LLC shall not be liable for any personal injury, property or other damages of any nature, whether compensatory, consequential, exemplary, or otherwise, resulting from any publication, use or reliance upon the information herein.

**Date of preparation / last revision:** 08/29/2016 / -**Abbreviations and acronyms:**

ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road  
 ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways  
 IMDG: International Maritime Code for Dangerous Goods  
 DOT: US Department of Transportation  
 IATA: International Air Transport Association  
 ACGIH: American Conference of Governmental Industrial Hygienists  
 EINECS: European Inventory of Existing Commercial Chemical Substances  
 ELINCS: European List of Notified Chemical Substances  
 CAS: Chemical Abstracts Service (division of the American Chemical Society)  
 NFPA: National Fire Protection Association (USA)  
 HMIS: Hazardous Materials Identification System (USA)  
 LC50: Lethal concentration, 50 percent  
 LD50: Lethal dose, 50 percent  
 PBT: Persistent, Bioaccumulative and Toxic  
 vPvB: very Persistent and very Bioaccumulative  
 NIOSH: National Institute for Occupational Safety  
 OSHA: Occupational Safety & Health  
 TLV: Threshold Limit Value  
 PEL: Permissible Exposure Limit  
 REL: Recommended Exposure Limit  
 Press. Gas: Gases under pressure – Compressed gas  
 Press. Gas: Gases under pressure – Dissolved gas  
 Acute Tox. 3: Acute toxicity – Category 3  
 Skin Corr. 1B: Skin corrosion/irritation – Category 1B  
 Skin Irrit. 2: Skin corrosion/irritation – Category 2  
 Eye Irrit. 2A: Serious eye damage/eye irritation – Category 2A

**Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) +1-877-204-9106